

DOWNLIGHT LIGHTING

Introducing the  
**POZZO DELTA**



The **POZZO DELTA** is a circular recessed luminaire available in three sizes with height adjustable circular microprism acrylic diffuser to provide two appearances for the lighting of offices, reception areas, public spaces and medical facilities. The microprism diffuser provides a low glare solution for offices.

**LIGHTING**  
**INNOVATIONS**  
**AFRICA**

A member of the Fagerhult Group

**Connecting** Light.  
Creating **Life.**








## Product Features

- Housing in die-cast aluminium – powder coated with structured finish
- Opal acrylic diffuser
- Integral LED driver
- Available in CCT 3000K and 4000K
- Options include DALI dimming, emergency and Li-Connect Bluetooth mesh control
- LED life  $L_{80B_{10}}$  – 50 000 hours
- Driver life  $F_{10}$  – 100 000 hours
- Supply – 220–240V 50–60Hz PF > 0.95
- Surge current (flicker) < 5%
- 5 year guarantee

### POZZO DELTA $\varnothing$ 383




104 lm/W





Luminaire Wattage	Luminaire Output (Lumens)	Colour Temperature	Efficacy lm/W	Ra (CRI)	Reference Code
15W	1 480	3000K	99	>80	24285
15W	1 554	4000K	104	>80	24286

### POZZO DELTA $\varnothing$ 483



124 lm/W



Luminaire Wattage	Luminaire Output (Lumens)	Colour Temperature	Efficacy lm/W	Ra (CRI)	Reference Code
21W	2 471	3000K	118	>80	24290
21W	2 595	4000K	124	>80	24291

## Efficacy Rating



**PREMIUM RANGE** >140 lm/W




**MID RANGE** 120 - 140 lm/W





**ECO RANGE** 100 - 120 lm/W

### POZZO DELTA $\varnothing$ 583



131 lm/W



Luminaire Wattage	Luminaire Output (Lumens)	Colour Temperature	Efficacy lm/W	Ra (CRI)	Reference Code
29W	3 617	3000K	125	>80	24293
29W	3 798	4000K	131	>80	24294

